

Product Specifications

Fixed Height Bathtub GK COMPACT

Description

- Tub body and casing constructed of fibreglass with a gelcoated surface
- 4 height-adjustable feet
- Circulating rubber protection for tub
- Ergonomically designed tub ensures greater movement for user and ease of use by the care giver
- Tub body with incorporated grooves for tub shorter plate
- Adjustment of temperature via thermostatic mixing valve with electronic (solar powered) monitoring of temperature for fill in and shower
- Patient shower with white hose 2,100 mm (6' 11") and self-closing valve
- Manual drain assembly
- Standard, commercially available valves and fittings
- System is free-standing

Technical Specifications

Connections:

- Hot and cold water, connector ½"
- Drain Ø 50 mm (2")

Dimensions:

- Width: 830 mm, Length: 2065 mm

Working Height:

- Adjustable from 695 mm – 945 mm
(with tools manually adjustable in steps of 50 mm)

Water Consumption for a Bath:

- Approx. 250 litres

Certificates

- CE mark

Make: Krämer
Type: GK COMPACT M
Art.No.: 3.600.00

Product Specifications

Options for Fixed Height Bathtub GK COMPACT

Injector Disinfection

- Disinfection shower, operated via a manual shut-off valve, with red hose 2,000 mm (6' 7") and self-closing valve on handle
- System suitable for 5 L containers
- Feed of the disinfection liquid via injector and adjustable flow gauge

Make: Krämer
Type: GK COMPACT D
Art.No.: 3.800.10

Safety Bar in Pairs

- Two grab handles for additional support

Make: Krämer
Type: GK COMPACT HA
Art.No.: 3.800.40

Tub Shorter Plate GK Compact

- For smaller persons the foot space can be reduced by sliding the tub shorter plate, a plastic board with handle, into the corresponding incorporated grooves in the tub body.

Make: Krämer
Type: GK COMPACT WV
Art.No.: 3.700.80

Head Rest

- Can be fixed inside the tub via suction cup

Make: Krämer
Type: GK COMPACT KO
Art.No.: 1.500.90

Backflow Preventer 12/12

- Backflow preventer for the sanitary piping

Make: Krämer
Type: GK COMPACT SY
Art.No.: 6.200.93