Product Specifications

Shower Trolley GK PRIMUS 2000 HYD

mobile shower trolley with manual oil-hydraulic variable height adjustment

Description

- Shower trolley for showering and transporting of residents in hospitals, emergency services, health centres and nursing homes
- Infinitely variable height adjustment by means of a manual hydraulic pump
- For a problem free water drain the gas spring assisted Anti-Trendelenburg tilt of the stretcher surface is infinitely variable from 0°-15°.
- Head and back rest can be adjusted from 0° to +35° via stepwise adjustable fittings.
- The shower mattress area comes in one piece, is padded, detachable and has a flexible 1 m long drain hose.
- Lifting mechanism pivots are Teflon-lined.
- Metal framework galvanized and powder-coated
- Stable construction with four smooth-running 200 mm diameter castors.
- Central castor locking system with directional stability installation
- Equipped with two push handles
- Wall bumpers integrated at the corners for protection against wall damage
- Side rails drop down and are easily lockable.
- Optionally: Softly padded neck cushion

Technical Specifications

-	Load capacity170	kg
-	Net weight104	kg
-	Height adjustment via hydraulics600-950	
-	Maximum external dimensions:	
	Length2100	mm
	Width810	mm
-	Stretcher surface:	
	Length1900	mm
	Width650	mm
-	Length of head and back rest700	mm
-	Tilt of stretcher surface0°	
-	Tilt of head and back rest0°	to +35° (stepwise adjustable fittings)
-	Height of stretcher mattress border250	mm
-	Height of drop-down side rails220	mm
-	Length of drain hoseapprox. 1000	mm (integrated in stretcher mattress)
-	Diameter of castors200	mm

Certificates

- CE mark

Make: Krämer

Type: GK PRIMUS 2000 HYD

Art.No.: 7.200.00

Product Specifications

Options for GK PRIMUS 2000 HYD

Head Rest GK Primus

Make: Krämer Type: GK PRI 2000 KO Art.No.: 7.300.03

Mattress for GK Primus 2000

Make: Krämer Type: GK PRI 2000 AM Art.No.: 7.300.08